



Technical Data Sheet

Datasheet 30.06.10
Product Code: 1926001

Axter Limited

West Road Ransomes Europark
Ipswich Suffolk IP3 9SX
Tel (01473) 724056 Fax (01473) 723263
Email info@axterltd.co.uk

www.axter.co.uk

NB: The manufacturer reserves the right without prior notice to modify the composition of his products. Characteristics provided in this publication derive from data obtained under controlled test conditions. AXTER Limited makes no warranties, express or implied as to the properties and performance under any variations from such conditions in actual construction.

AXTER FILTER

INTRODUCTION	Axter Filter is a 2.4mm thick non woven synthetic layer of polyester fibre	
USAGE	It is used as a filter on roof gardens and retaining walls, in order to retain small particles of soil. It is applied over drainage boards.	
PACKAGING	Rolls of 200 m ² (100 m x 2 m) with a nominal weight of 41 kg.	
STORAGE	Rolls to be stored horizontally.	
COMPOSITION	Polyester (BS EN 29 073/1)	200gm/m ²
CHARACTERISTICS	Thickness (BS EN 29073/2)	2.4 mm
	Tensile strength (BS EN 10 319)	1.5 kN/m
	Elongation at break (BS EN 10319) Measure	≥ 60%
	of porosity (BS EN 12 956)	91 µm
	Permeability (BS EN 11 058)	25mm/s