



West Road
Ransomes Europark
Ipswich IP3 9SX



ETA-03/0049

Prepared
▶ 25/02/2009

Code
▶ 1534992
▶

PRODUCT DATA SHEET

WILOTEKT-PLUS SURFACE CONDITIONING PRIMER

Technical ref
▶ ETA-03/0049

INTRODUCTION

WILOTEKT-PLUS Surface Conditioning Primer is a fast drying, cold-applied bitumen-based primer.

USAGE

Bitumen-based primer used on all substrates (concrete, screeds, metal and timber) before the installation of Wilotekt-Plus structural waterproofing to provide a good key for the system and to protect the substrate from moisture.

PRESENTATION

Wilotekt-Plus Surface Conditioning Primer is packaged in 22kg drums. Coverage: one drum will cover 70m².

STORAGE

Wilotekt-Plus Surface Conditioning Primer must be stored in a well ventilated area. The product must be kept away naked flames and electrostatic charge. Shelf life (unsealed in original packaging): 1 year.

COMPOSITION

Solvent based bitumen.

CHARACTERISTICS

Density	Density	0.94+-0.05
	Width	54% +-2%
	Viscosity	15 to 20s
	Flash point	-10 deg.C +- 2 deg.C

The manufacturer reserves the right to modify, at any time, the characteristics of its products.