



West Road
Ransomes Europark
Ipswich IP3 9SX

www.axter.co.uk



BS EN 13707 0679-CPD-0128

Prepared
12/06/2009
Cancels and replaces

Code :
48E1186
Manufacture source
Gulf Seal

Technical ref:
FT AXTER

PRODUCT DATA SHEET

n° of certification organisation: 0679
Year mark was 1st fixed : 2006

TERRAGUM E 4mm Sand

DESCRIPTION

TERRAGUM E 4mm Sand is a polyester reinforced, APP polymer modified membrane.

USE

Cap sheet in roof waterproofing system in self-protected applications or under site applied added protection.

APPLICATION METHOD

Torched.

STORAGE

Rolls to be stored upright and away from heat.

COMPOSITION (indicative)

Reinforcement (gm/m ²) :	Polyester	180
Binder (gm/m ²) :	APP	4500
Surface finish (gm/m ²) :	Sand	300
Under surface finish (gm/m ²) :	Thermofusible film	10

CHARACTERISTICS

	STANDARD	UNITS	VALUES	Tolerance	
				Min	Max
Dimensions	EN 1848-1	Length	8	-0%	
		Width	1	-1%	
		Straightness	-	Pass	
Nominal thickness	EN-1849-1	mm	36		
Visible defects	EN-1850-1	-	4.00	3.80	4.20
Adhesion of granules	EN 12039	%	None		
Tensile properties : maximum tensile force	EN 12311-1	N/50 mm	NA	-	-
			Longitudinal	690	400
Tensile properties : elongation	EN 12311-1	%	Cross direction	560	680
			Longitudinal	30	15
Flexibility at low temperature	EN 1109	°C	Cross direction	55	65
			Longitudinal	-5	≤
Flow resistance at elevated temperature	EN 1110	°C	100	≥	
Dimensional stability	EN 1107-1	%	0.5	≤	
Reaction to fire	EN 13501-1	-	F		

NA=not applicable due to use of product.

The manufacturer reserves the right to modify, at any time, the characteristics of his products.