



# Technical Data Sheet

Datasheet 30.06.10  
Product Code: 1924010

## Axter Limited

West Road Ransomes Europark  
Ipswich Suffolk IP3 9SX  
Tel (01473) 724056 Fax (01473) 723263  
Email [info@axterltd.co.uk](mailto:info@axterltd.co.uk)

[www.axter.co.uk](http://www.axter.co.uk)

NB: The manufacturer reserves the right without prior notice to modify the composition of his products. Characteristics provided in this publication derive from data obtained under controlled test conditions. AXTER Limited makes no warranties, express or implied as to the properties and performance under any variations from such conditions in actual construction.

## BUTYL CORD

### Synthetic rubber extruded cord with talc coating to eliminate adhesion during storage and use

<b>USE</b>	Component within the EXCELJOINT movement/expansion joint system.
<b>PACKAGING</b>	Cord diameter: 3 cm Cord length: 5 m Cord weight: 5 kg  Packed in boxes (2 per box)
<b>STORAGE</b>	Shelf life (unsealed in its original packaging): 1 year.
<b>CHARACTERISTICS</b> <i>binder</i>	Installation temperature: $+ 5^{\circ}\text{C} \leq T \leq + 40^{\circ}\text{C}$ Service temperature: $- 20^{\circ}\text{C} \leq T \leq \text{to } 80^{\circ}\text{C}$  No water absorption.