



# Technical Data Sheet

Datasheet 30.06.10  
Product Code: 1926001

## Axter Limited

West Road Ransomes Europark  
Ipswich Suffolk IP3 9SX  
Tel (01473) 724056 Fax (01473) 723263  
Email [info@axterltd.co.uk](mailto:info@axterltd.co.uk)

[www.axter.co.uk](http://www.axter.co.uk)

NB: The manufacturer reserves the right without prior notice to modify the composition of his products. Characteristics provided in this publication derive from data obtained under controlled test conditions. AXTER Limited makes no warranties, express or implied as to the properties and performance under any variations from such conditions in actual construction.

# AXTER FILTER

<b>INTRODUCTION</b>	<b>Axter Filter is a 2.4mm thick non woven synthetic layer of polyester fibre</b>	
<b>USAGE</b>	It is used as a filter on roof gardens and retaining walls, in order to retain small particles of soil. It is applied over drainage boards.	
<b>PACKAGING</b>	Rolls of 200 m <sup>2</sup> (100 m x 2 m) with a nominal weight of 41 kg.	
<b>STORAGE</b>	Rolls to be stored horizontally.	
<b>COMPOSITION</b>	Polyester (BS EN 29 073/1)	200gm/m <sup>2</sup>
<b>CHARACTERISTICS</b>	Thickness (BS EN 29073/2)	2.4 mm
	Tensile strength (BS EN 10 319)	1.5 kN/m
	Elongation at break (BS EN 10319) Measure	≥ 60%
	of porosity (BS EN 12 956)	91 µm
	Permeability (BS EN 11 058)	25mm/s