



Technical Data Sheet

January 2004
Product Code: 1608001

Axter Limited

West Road Ransomes Europark
Ipswich Suffolk IP3 9SX
Tel (01473) 724056 Fax (01473) 723263
Email info@axterltd.co.uk

www.axter.co.uk

NB: The manufacturer reserves the right without prior notice to modify the composition of his products. Characteristics provided in this publication derive from data obtained under controlled test conditions. AXTER Limited makes no warranties, express or implied as to the properties and performance under any variations from such conditions in actual construction.

MASTIC HYRENE

INTRODUCTION	MASTIC HYRENE is a cold applied bituminous adhesive
USE	Used as an adhesive for installing thermal insulation. Used for partially bonding waterproofing systems onto concrete decks.
COVERAGE	Depending upon the type of support, insulation etc. 1kg will cover between 2 and 2.5 m ² .
PACKAGING	25 kg drums
STORAGE	Keep away from heat and naked flames. Shelf life (unsealed in its original packaging): 1 year.
COMPOSITION	Bitumen with added solvents.
CHARACTERISTICS	Dry extract 77% Viscosity @ 25°C (NFT 30 029) 17 000 to 22 000 mPa.s
COMMENTS	This product contains flammable products. Safety precautions to be taken when using this product are described in the MASTIC HYRENE COSHH ⁽¹⁾ sheet. Contact Axter for details.
	<small>⁽¹⁾ Control of Substances Hazardous to Health</small>