



Technical Data Sheet

Datasheet 11.12.09
Product Code: 1966001
Technical Reference: Starcoat R Cahier des Charges

Axter Limited

West Road Ransomes Europark
Ipswich Suffolk IP3 9SX
Tel (01473) 724056 Fax (01473) 723263
Email info@axterltd.co.uk

www.axter.co.uk

NB: The manufacturer reserves the right without prior notice to modify the composition of his products. Characteristics provided in this publication derive from data obtained under controlled test conditions. AXTER Limited makes no warranties, express or implied as to the properties and performance under any variations from such conditions in actual construction.

MATCOAT R

MATCOAT R is a woven nylon jersey reinforcement material

USE

Reinforcement for details, such as internal and external angles.

PACKAGING

Rolls of 50m x 0.15m

STORAGE

- Store in a cool, well ventilated place
- Protect from heat, direct sunlight and extremes of temperature
- Store at temperatures between 5°C and 35°C

CHARACTERISTICS

Surface mass (DIN 53352)	>70g/m ²
Tensile force (DIN 53857): longitudinal	66N/cm
Resistance to tearing (DIN 53857): cross direction	75%

GENERAL

MATCOAT R is sandwiched between two layers of STARCOAT R.

Use scissors to cut appropriately sized pieces for the details and apply to the first layer of STARCOAT R while still liquid.

Ensure a minimum overlap of 10mm between each piece of MATCOAT R.

Apply pressure with a dry brush to ensure full bonding with no blistering.