



Technical Data Sheet

January 2011

Axter Limited

West Road Ransomes Europark
Ipswich Suffolk IP3 9SX
Tel (01473) 724056 Fax (01473) 723263
Email info@axterltd.co.uk

www.axter.co.uk

NB: The manufacturer reserves the right without prior notice to modify the composition of his products. Characteristics provided in this publication derive from data obtained under controlled test conditions. AXTER Limited makes no warranties, express or implied as to the properties and performance under any variations from such conditions in actual construction.

PLASTORIV

Description

Axter Plastoriv is used for the installation of thermal insulation and / or single or multi layer waterproofing systems to profiled metal roof decks (0.75 to 1.5mm thick). It comprises a white polyamide washer and a Supracoat 2C coated, self-drilling steel screw with 15 Kesternich cycles resistance.

Benefits

The use of Plastoriv eliminates the risk of cold bridging. As they are pre-assembled, there is no need for a washer to be mounted on site which saves time.

Sizes

Plastoriv is available in a number of sizes depending on the build up thickness.

Build up thickness (mm)	Washer length (mm)	Screw length (mm)	Unit/box
60	50	45	500
70	50	60	500
80	50	70	500
90	50	80	500
100	70	70	500
110	70	80	400
120	90	70	400
130	90	80	400
140	110	70	400
150	110	80	400
160	130	70	300
170	130	80	300
180	150	70	300
190	150	80	300
200	150	90	300
210	150	100	200
220	130	130	200
230	150	120	200
240	150	130	200
250	150	150	200
260	150	150	200
270	130	180	200
280	150	180	200
290	150	180	150
300	150	200	100
310	150	200	100

