



West Road
Ransomes Europark
Ipswich IP3 9SX

www.axter.co.uk



Prepared

▶ 27/02/2009

▶ Cancels and replaces



▶ Code :

▶ 1563005



▶ Technical ref:

▶ FT AXTER

PRODUCT DATA SHEET

STICKBAND

INTRODUCTION

Stickband is a self-adhesive waterproofing strip made up of a mastic butyl based, self-adhesive binder and protected by an aluminium foil. The under surface is a peel-off silicone film. Thickness is approximately 0.6mm.

USAGE

In particular for use with the Wilotekt-Plus system to seal gaps in the substrate. Also used on new and refurbishment projects on the following: waterproof joints on metal decks (vapour control layer for profiled metal decks); channels, gutters, pipework, rainwater outlets, kerbs, covers (zinc, aluminium, galvanised steel, lead); waterproofing for other detailing work (bridging cracks, flashings, etc). Stickband is cold bonded to decks that are clean, dry, sound (not porous or friable) without a primer. If the deck is porous or friable, apply primer (Vernis Antac 300gm/m²).

PACKAGING

Stickband is available in the following roll sizes:

- 10m x 5cm , average weight 0.55 kg (16 rolls/box)
- 10m x 7.5cm , average weight 0.825 kg (8 rolls/box)
- 10m x 10cm , average weight 1.100 kg (8 rolls/box)
- 10m x 15cm , average weight 1.650 kg (4 rolls/box)
- 10m x 20cm , average weight 2,200 kg (4 rolls/box)
- 10m x 30cm , average weight 3.3 kg (4 rolls/box)
- 10m x 45cm , average weight 4.95 kg (4 rolls/box)

STORAGE

Rolls must be stored in cardboard in a dry, ventilated place, in a maximum temperature of 30°C, away from any source of heat or fire, for a maximum period of 12 months. Storage in temperatures above 30°C can cause problems when removing the silicone during installation. Rolls must be protected from frost.

COMPOSITION

Binder : Extruded butyl rubber
Surface finish: Plastic film/aluminium
Under surface finish : Silicone film

The manufacturer reserves the right to modify, at any time, the characteristics of its products.