



TECHNICAL DATASHEET

AXTER TIMBER DECKING SUPPORTS

November 2013

Adjustable support for wood decking


For wood decking on flat roof amenity areas, Axter offers a timber decking support attachment that fits directly on to the Axter fixed/adjustable paving slab supports without the need for fixings or adhesive*. This accessory is designed to support a timber bearer or joist onto which the decking can be fastened.

This means that it is easy to install flat decking over a laid to falls flat roof. The joists are held clear of the roof itself, increasing their life and allowing a free passage of water to outlets.


Advantages

Perforations in the head prevent water stagnation at the points of contact with the timber joist, prolonging the life of the timber decking.

View from above



The device fits easily on to the wings of the Axter paving slab support*. No fixings or adhesive are required.



Composition

Copolymer polypropylene with calcium carbonate.

Size

Diameter: 120mm
Height: 60mm
Packaging: 120 units/box

Minimum joist size 50mm

*Axter paving slab supports are available in the following sizes:

Fixed: 35mm
Adjustable: 40/60, 60/90,
90/150, 150/260mm

Note: the Timber Decking Support is sold as a separate unit for attachment to Axter paving slab supports.

Joist mechanically fixed at right angles to the oblong holes in the support head.



The manufacturer reserves the right without prior notice to modify the composition of these products. Characteristics provided in this publication derive from data obtained under controlled test conditions. Axter Ltd makes no warranties, express or implied, as to the properties and performance under any variations from such conditions in actual construction.