

DECLARATION OF PERFORMANCE

No: 'C' (Concrete) Fixing 1.0 EN (ETA08/0285 Annex 1:12)

1	Identification Code	'C' Concrete Fixing
2	Batch number allowing identification of the construction product	Refer to the product label
3	Intended use	Fastening of thermal insulation and waterproofing systems on external roofs to substrates of concrete/lightweight concrete/wood.
4	Manufacturer	Axter Ltd West Road, Ransomes Europark IPSWICH, Suffolk IP3 9SX www.axter.co.uk/dop
5	Authorised representative	NA
6	System of assessment and verification of constancy of performance of the product	2+
7	Product covered by the harmonized standard	
8	European Technical Assessment	Sintef Building and Infrastructure ETAG 006, ETA-08/0285 Sintef Building and Infrastructure 2+ 1071-CPD-1510
9	Declared performance	

Essential characteristics	Performance	Harmonised technical specification
ETAG 006 5.3.7.1 Corrosion resistance	15 cycles (2L SO ₂)	See ETA-08/0285
ETAG 006 5.3.4.2 Testing of resistance to unwinding	Passed	See ETA-08/0285
ETAG 006 5.3.4.1 Axial loading test (pull out)	See ETA-08/0285	See ETA-08/0285

10 Ecology, health and safety information

As per the EC regulation 1907/2006 (REACH) Article 31 a safety data sheet is not required for putting into circulation and placing on the market or using this item. If the item is used as intended and disposed of (disposal or recovery) as per the applicable legislation, the environment is not harmed. This item does not contain any substances that are released under normal conditions or foreseeable conditions of use. There are therefore no registration requirements for substances in this item in the context of Article 7 paragraph 1 of the regulation. Based on our current knowledge this item does not contain any SVHC (Substances of Very High Concern) in concentrations over 0.1% (w/w) weight as per the candidate list published by the European Chemicals Agency (ECHA).

11 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:
Phillip Wilcox-Moore (Managing Director)



Ipswich, July 1, 2013