


- 1 ECOLINE ADH fleeceback
single ply membrane fully bonded
using ADH Adhesive
- 2 Hytherm tapered/flat board Insulation
mechanically fixed with Ecoline insulation
washers and fixings (thickness to achieve
design U-value and/or design fall)
- 3 Vernis Antac ST primer
- 4 Axter Vapour Control Layer
- 5 ECOLINE Tubular Washer and
mechanical fastener (MTP) fixing
- 6 Longitudinal /Transversal Lap Joint
(with heat welded seam - 40mm)
- 7 Plywood substrate
(by specialist subcontractor)
- 8 ADH Adhesive



Do Not Scale. All dimensions to be checked on site by the Axtershield Installer

Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT	AXTER - STANDARD DETAIL		DRAWING AXTER WARM ROOF - ECOLINE ADH SYSTEM TRANSVERSAL/LONGITUDINAL JOINT DETAIL - PLYWOOD SUBSTRATE			
	CLIENT	N/A	DWG.No WR.P.EL.adh.140	SCALE 1:5 @ A4	DATE 10.16	REV N/A



www.axter.co.uk
info@axterltd.co.uk
01473 724 056

Axter Ltd.
West Road, Ransomes Europark,
Ipswich, Suffolk, IP3 9SX